


# Domekt R 450 V

Maximal air flow, m <sup>3</sup> /h	472
Panel thickness, mm	50
Unit weight, kg	71
Supply voltage, V	1~230
Maximal operating current, A	HE 7,1
Thermal efficiency of heat recovery, %	85
Reference flow rate, m <sup>3</sup> /s	0,092
Reference pressure difference, Pa	50
SPI, W/(m <sup>3</sup> /h)	0,44
Filters dimensions BxHxL, mm	470x240x46-M5
Electric power input of the fan drive at reference flow rate, W	72
Electric power input of the fan drive at maximum flow rate, W	170
Electric air heater capacity, kW / Δt, °C	1 / 8,4
Control panel	C6.1 / C6.2
Maintenance space, mm	500



The photo is intended for informational purposes only, exact details may vary.

### Acoustic data

**A-weighted sound power level L<sub>WA</sub>, dB(A) at reference flow rate**

Supply inlet	58
Supply outlet	72
Exhaust inlet	58
Exhaust outlet	72
Casing	39

**A-weighted sound pressure level L<sub>PA</sub>, dB(A)**  
10 m<sup>2</sup> normally isolated room, distance from casing – 3 m.


Surroundings	29
--------------	----

### Temperature efficiency


	Winter					Summer		
Outside temperature, °C	-23	-15	-10	-5	0	25	30	35
After heat exchanger*, °C	14,3	15,7	16,5	17,4	18,2	22,5	23,4	24,2

\* indoor +22°C, 20% RH


### Performance




Shown as left (L1)



Shown as right (R1)



- A outdoor intake
- B supply air
- C extract indoor
- D exhaust air
- E additional extraction connection (by-pass – extraction without heat recovery)



### Accessories

Closing damper	AGUJ-M-160+LF230/LM230
Silencer	A/D AGS-160-50-600-M
	B/C AGS-160-50-900-M
Water heater	DH-160
PPU	PPU-HW-3R-15-0,4-W1

2-way valve (water heater)	VVP47.10-0,4
Air heater-cooler	DCW-0,5-3 / DHCW-160
2-way valve (water cooler)	VVP47.10-1,6
DX cooler	DCF-0,5-3